

ROULEAUX À ROULEMENTS NORMALISÉS – Type : RAS


- Embouts tôle acier, roulements normalisés, $-20^{\circ}\text{C} < T < +80^{\circ}\text{C}$
- Finition : acier brut, galvanisé et zingué



Type RAS	Capacités en (kg) charge uniformément répartie															
Ø Rouleaux	Axe/Lg	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500
40 x 1,5	12	64	64	64	64	64	53	46	40	36	32	29	26	24	22	20
	15	77	77	77	77	77	64	55	48	43	38	35	31	29	26	24
50 x 2	12	130	130	130	130	110	92	79	69	62	55	50	46	42	39	37
	15	130	130	130	130	130	130	120	105	93	85	76	70	65	60	56
60 x 2	12	160	160	160	160	125	107	94	84	77	72	65	61	57	54	50
	15	250	250	250	250	250	206	178	156	140	127	116	107	100	94	88
63,5 x 2,9 70 x 2	15	250	250	250	250	250	206	178	156	140	127	116	107	100	94	88

ROULEAUX À ROULEMENTS NORMALISÉS LOURDS – Type : RAU - RAV

- Roulements normalisés, boîtier en tôle, soudé pour le RAV, $-20^{\circ}\text{C} < T < +80^{\circ}\text{C}$
- Finition : acier brut, zingué



Type RAU	Capacités en (kg) charge uniformément répartie															
Ø Rouleaux	Axe/Lg	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500
50 x 5	20	400	400	400	320	320	270	235	205	180	162	150	137	126	117	110
55 x 5	20	600	600	600	600	600	500	425	375	330	300	270	250	230	210	200
63,5 x 2,9	20	300	300	300	250	250	250	235	205	180	162	150	137	126	117	110
70 x 2,9 80 x 2	20	320	320	320	320	320	270	235	205	180	162	150	137	126	117	110
89 x 3,2	20	500	500	500	500	500	500	425	375	330	300	270	250	230	210	200

Type RAV	Capacités en (kg) charge uniformément répartie															
Ø Rouleaux	Axe/Lg	100	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500
70 x 5 89 x 3	25	1050	1050	1050	1050	900	755	645	565	500	450	410	375	345	320	300
133 X 4 159 X 4	30	1500	1500	1500	1500	1365	1365	1280	1130	1000	900	820	750	700	640	600

