



Lift:UXB16-10/10 1785x2244 RAL5019

Item Attributes	
Attribute	Value
Table Type	UXB16
Number of Cylinders	2 psc
No. Scissor Height	1 psc
No. Scissor Length	1 psc
No. Scissor Width	1 psc
Labelled Capacity	1600 kg
Capacity	1600 kg
Installed Stroke	1000 mm
Designed Stroke	1000 mm
Closed Height	91 mm
Length	1785 mm
Width	2244 mm
Load Width	1000 mm
Pallet Size	1200x800,1200x1000 mm
Lifting Speed	71 mm/s
Lifting Time	15 sec
Output	3.9 kW
Power Supply	400 AC 3~/PE
Frequency	50 Hz
Rated Current	6.6 A
Control Voltage	24 DC V
Power Pack Placement	EXT, 3M
Protection Class	IP55
Hydraulic Oil	ISO 32
Surface Treatment	K2_02
Colour	RAL5019
Lift Category	1
Product Standard	Not Used
Platform Shape	Special
Declaration	IIB
Cylinder	80/40-250-430_GXM,
Operating Pressure	180 Bar
Idle Pressure	Not Defined bar
Flow	11 litre/min
Power Pack	K 3,9kW 100 7,4cc 30L 4P

Item Attributes	
Attribute	Value
Allowed Persons	0
Frame Length	1642 mm
Frame Width	2164 mm
Operating Temp	-20 - +50 °C
Hydraulic Drawing	406225A
Electric Drawing	1115757
Power Pack Drawing	0
Label Compilation	1105598
Marco Designation	MUXB16-10/8
Hymo Designation	UXB16-10/10
Jihab Designation	JX-16/100-2C
Saxon Designation	Not Defined
Price List Item	Yes
Price List Ref	UXB16-10/10